

# Mura

**Designer:** Woven Image

**Application(s):** Walls, Workstations, Partitions

## Composition & Pattern

**Composition** 100% PET (60% post-consumer recycled)

**Colours Available** 28

## Dimensions & Weight

**Dimensions** Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m and 105m

**Unit of Sale** Linear metre

**Unit of Sale Net Weight (kg)** 0.424

## Performance

**Fire Test Result** ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS 476: Class 2, ASTM E84 Adhered: Class 1 or A, BS EN 45545-2 + A1 Annex C: CIT: 0.00

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016)

**Noise Reduction Coefficient (NRC) Result** Direct fix: 0.10

**Sound Absorption Average (SAA)** Direct fix: 0.08  
**Result**

**Weighted Sound Absorption Coefficient (αw)** Direct fix: 0.10 (H)  
**Result**

**Additional Acoustic Information** Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency

**Colour Fastness to Light Standard** ISO 105 B02  
**Test Method**

**Colour Fastness Light Rating** 6

**Colour Fastness to Rubbing Standard** ISO 105 - X12  
**Test Method**

**Colour Fastness to Rubbing Rating** Wet: 5, Dry: 5

## Sustainability

**VOC Emissions Results** ASTM D5116: TVOC Emissions Rate: <0.02mg/m<sup>2</sup>/hr (7 days)

**Sustainability Performance**



**Declare.**



**EPD®**  
AUSTRALASIA  
ENVIRONMENTAL PRODUCT DECLARATION  
EPD REGISTRATION NUMBER: 5-P-01142

## Instructions

**Additional Information** See Woven Image Mura Care & Cleaning Guide, and Installation Guide.

Please note: The face of Mura is smooth and the back is fluffy.  
Mura is rolled Face out on the core.

Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.