

# Curtain

**Designer:** Woven Image

**Application(s):** Walls

## Composition & Pattern

**Composition** 100% PET (51% post-consumer recycled)

**Colours Available** 8

**Pattern Type** Formed

## Dimensions & Weight

**Dimensions** Length: 2800mm (+/-5mm) Width: 975mm (+10mm/-5mm) Depth: 45mm (+/-5mm) Thickness: 9mm (+/-7%)

**Unit of Sale** Panel

**Unit of Sale Net Weight (kg)** 7

## Performance

**Fire Test Result** ISO 9705: Group 2, BS EN 13501.1: Classification B - s1, d0, ASTM E84 Unadhered: Class 1 or A

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17

**Noise Reduction Coefficient (NRC)** Direct Fix: 0.60

## Result

**Sound Absorption Average (SAA)** Direct Fix: 0.60  
**Result**

**Weighted Sound Absorption Coefficient ( $\alpha_w$ )** Direct Fix: 0.50 (MH)  
**Result**

**Sound Absorption Class** D (Direct fix)

**Colour Fastness to Light Standard** ISO 105 B02  
**Test Method**

**Colour Fastness Light Rating** 7

**Colour Fastness to Rubbing Standard** ISO 105 - X12  
**Test Method**

**Colour Fastness to Rubbing Rating** Wet: 5, Dry: 5

## Sustainability

**VOC Emissions Results** ASTM D5116 Rate: 0.015 mg/m<sup>2</sup>/hr (7 days); CDPH Standard Method v1.2 (CA 01350); TVOC Emissions Rate: 0.010mg/m<sup>3</sup>; Formaldehyde Emission Rate: <5 µg/m<sup>3</sup>

### Sustainability Performance



**Declare.**



## Instructions

**Additional Information** See Woven Image Embossed and 3D Formed Panels Care & Cleaning Guide.  
See Woven Image 3D Formed Installation Guide.

Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.

