

Zen Embossed Panel

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition	100% PET (51% recycled)
Colours Available	25
Pattern Type	Embossed

Dimensions & Weight	
Dimensions	Length: 2800mm (+/-3mm), Width: 1130mm (+/- 3mm), Thickness: 9mm (+/- 7%)
Unit of Sale	Panel
Unit of Sale Net Weight (kg)	8.13

Performance	
Fire Test Result	ASTM E84 Unadhered: Class 1 or A, BS EN 13501.1: Classification B - s1, d0, ISO 9705: Group 1, GB 8624 2012 Classification: B1(C- s2,d0)
Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016), ASTM C423 - 17, AS ISO 11654: 2002 (2016)

Noise Reduction Coefficient (NRC) Result	Direct fix: 0.30, 20mm air gap: 0.50, 50mm air gap: 0.70 Achieves an NRC of 0.75 with a 18mm acoustic backing
Weighted Sound Absorption Coefficient (aw) Result	Direct fix: 0.20 (H), 20mm air gap: 0.35 (MH), 50mm air gap: 0.60 (MH). Achieves an aw of 0.75 with a 18mm acoustic backing
Sound Absorption Class	E (Direct fix), D (20mm air gap), C (50mm air gap)
Additional Acoustic Information	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	6
Colour Fastness to Rubbing Standard Test Method	ISO 105 - X12
Colour Fastness to Rubbing Rating	Wet: 4 - 5, Dry: 5

Sustainability



Additional Information	See Woven Image Embossed Panels Care & Cleaning Guide. See Woven Image Embossed Panels Installation Guide.
	Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.

To assist in accurate pattern matching on a continuous wall, ZEN has been trimmed on all four sides with a unique 5 degree bevel as shown below. Dimensions shown in millimetres.