

Curtain

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition 100% PET (51% post-consumer recycled)

Colours Available 8

Pattern Type Formed

Dimensions & Weight

Dimensions Length: 2800mm (+/-5mm) Width: 975mm (+10mm/-5mm) Depth: 45mm (+/-5mm) Thickness: 9mm (+/-7%)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 7

Performance

Fire Test Result ISO 9705: Group 2, BS EN 13501.1: Classification B - s1, d0, ASTM E84 Unadhered: Class 1 or A

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17

Noise Reduction Coefficient (NRC) Direct Fix: 0.60

Result

Sound Absorption Average (SAA) Direct Fix: 0.60
Result

Weighted Sound Absorption Coefficient (α_w) Direct Fix: 0.50 (MH)
Result

Sound Absorption Class D (Direct fix)

Colour Fastness to Light Standard ISO 105 B02
Test Method

Colour Fastness Light Rating 7

Colour Fastness to Rubbing Standard ISO 105 - X12
Test Method

Colour Fastness to Rubbing Rating Wet: 5, Dry: 5

Sustainability

VOC Emissions Results ASTM D5116 Rate: 0.015 mg/m²/hr (7 days); CDPH Standard Method v1.2 (CA 01350); TVOC Emissions Rate: 0.010mg/m³; Formaldehyde Emission Rate: <5 µg/m³

Sustainability Performance



Declare.



Instructions

Additional Information See Woven Image Embossed and 3D Formed Panels Care & Cleaning Guide.
See Woven Image 3D Formed Installation Guide.

Exact colour matching cannot be guaranteed between batches.
Fibre mix and web variation are natural characteristics of this product.

