

Column

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition 100% PET (51% post-consumer recycled)

Colours Available 8

Pattern Type Formed

Dimensions & Weight

Dimensions Length: 2800mm (+/-5mm), Width: 995mm (+10/-5mm), Depth: 70mm (+/-5mm), Thickness: 9mm (+/-7%)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 7.6

Performance

Fire Test Result ISO 9705: Group 2, BS EN 13501.1: Classification B - s1, d0, ASTM E84 Unadhered: Class 1 or A

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17

Noise Reduction Coefficient (NRC) Direct Fix: 0.65

Result

Sound Absorption Average (SAA) Result	Direct Fix: 0.67
Weighted Sound Absorption Coefficient (α_w) Result	Direct Fix: 0.65 (H)
Sound Absorption Class	C (Direct fix)
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	7
Colour Fastness to Rubbing Standard Test Method	ISO 105 - X12
Colour Fastness to Rubbing Rating	Wet: 5, Dry: 5

Sustainability

VOC Emissions Results ASTM D5116 Rate: 0.015 mg/m²/hr (7 days); CDPH Standard Method v1.2 (CA 01350); TVOC Emissions Rate: 0.010mg/m³; Formaldehyde Emission Rate: <5 µg/m³

Sustainability Performance



Declare.



Instructions

Additional Information See Woven Image Embossed and 3D Formed Panels Care & Cleaning Guide.
See Woven Image 3D Formed Installation Guide.

Exact colour matching cannot be guaranteed between batches.
Fibre mix and web variation are natural characteristics of this product.

