

## Ascent Tile

**Designer:** Woven Image

**Application(s):** Walls

### Composition & Pattern

**Composition** 100% PET (67% post-consumer recycled)

**Hardware Composition** Ascent Tile Infill: 100% PET (60% recycled), and Clips: Polycarbonate resin

**Colours Available** 17

**Pattern Type** Formed

### Kit & Box Content

**Box Contents** 6 x Ascent Tiles & 1 x bag of clips

**Component Details** 16 clips with screws included. Additional acoustic infill can be requested upon ordering.

### Dimensions & Weight

**Dimensions** Ascent Tile: Length: 900mm (+/- 5mm), Width: 500mm (+/- 5mm), Depth: 50mm (+/- 5mm), Thickness: 4mm (+/- 0.5mm) Ascent Tile Infill: Length: 890mm (+/- 2mm), Width: 480mm (+/- 2mm), Thickness: 25mm (+/- 2mm)

**Unit of Sale** Box

**Unit of Sale Net Weight (kg)** 5.8

## Performance

<b>Fire Test Result</b>	AS 3837: Group 3, ASTM E84 Unadhered: Class 1 or A, BS EN 13501.1: Classification B - s1, d0, GB 8624 B1
<b>Acoustic Performance Standard Test Method</b>	AS ISO 354: 2006 (R2016)
<b>Noise Reduction Coefficient (NRC) Result</b>	Direct fix: 0.70 Ascent Tile & Infill: 0.90
<b>Sound Absorption Average (SAA) Result</b>	Direct fix: 0.66
<b>Weighted Sound Absorption Coefficient (<math>\alpha_w</math>) Result</b>	Direct fix: 0.60 (MH), and Ascent Tile & Infill: 0.90
<b>Sound Absorption Class</b>	C (Direct fix)
<b>Additional Acoustic Information</b>	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency
<b>Colour Fastness to Light Standard Test Method</b>	ISO 105 B02
<b>Colour Fastness Light Rating</b>	6
<b>Other Testing</b>	Ascent Tile Infill Fire Test ISO 9705: Group 1

## Sustainability

<b>VOC Emissions Results</b>	ASTM D5116: TVOC Emissions Rate: <0.011mg/m <sup>2</sup> /hr (7 days), and CDPH Standard Method v1.2: TVOC Emissions Rate: <0.010mg/m <sup>3</sup> ; Formaldehyde Emissions Rate: <2 $\mu$ g/m <sup>3</sup>
------------------------------	---

## Sustainability Performance






Declare. 




## Instructions

**Additional Information** See Woven Image Mura Unprinted Composite Panels and Tiles Care & Cleaning Guide.  
See Woven Image Ascent Tile Installation Guide.


Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.




6 x Ascent Tiles



4 x A clip



8 x B clip



4 x C clip