

## Column

**Designer:** Woven Image

**Application(s):** Walls

### Composition & Pattern

**Composition** 98.5% PET (50% post-consumer recycled), 1.5% PE

**Colours Available** 8

**Pattern Type** Formed

### Dimensions & Weight

**Dimensions** Length: 2800mm (+/-5mm), Width: 995mm (+10/-5mm), Depth: 70mm (+/-5mm), Thickness: 9mm (+/-7%)

**Unit of Sale** Panel

**Unit of Sale Net Weight (kg)** 7.6

### Performance

**Fire Test Result** BS EN 13501.1: Classification B - s1, d0, ASTM E84 Unadhered: Class 1 or A, ISO 9705: Group 1

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016)

**Noise Reduction Coefficient (NRC)** Direct Fix: 0.65

## Result

**Sound Absorption Average (SAA) Result** Direct Fix: 0.67

**Weighted Sound Absorption Coefficient ( $\alpha_w$ ) Result** Direct Fix: 0.65 (H)

**Sound Absorption Class** C (Direct fix)

**Colour Fastness to Light Standard Test Method** ISO 105 B02

**Colour Fastness Light Rating** 7

**Colour Fastness to Rubbing Standard Test Method** ISO 105 - X12

**Colour Fastness to Rubbing Rating** Wet: 5, Dry: 5

## Sustainability

**VOC Emissions Results** ASTM D5116 Rate: 0.015 mg/m<sup>2</sup>/hr (7 days); CDPH Standard Method v1.2 (CA 01350); TVOC Emissions Rate: 0.010mg/m<sup>3</sup>; Formaldehyde Emission Rate: <5 µg/m<sup>3</sup>

### Sustainability Performance



**Declare.**



## Instructions

**Additional Information**

See Woven Image Embossed and 3D Formed Panels Care & Cleaning Guide.

See Woven Image 3D Formed Installation Guide.

Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.

