Mura™

Designer: Woven Image

Application(s): Walls, Workstations, Partitions

Composition & Pattern

Composition	100% PET (60% post-consumer recycled)
Colours Available	29

Dimensions & Weight

Dimensions	Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m and 105m
Unit of Sale	Linear metre
Unit of Sale Net Weight (kg)	0.424

Performance

Fire Test Result	ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS 476: Class 2, ASTM E84 Adhered: Class 1 or A, BS EN 45545-2 + A1 Annex C: CIT: 0.00
Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016)
Noise Reduction Coefficient (NRC) Result	Direct fix: 0.10

Copyright Woven Image

Sound Absorption Average (SAA) Result	Direct fix: 0.08
Weighted Sound Absorption Coefficient (αw) Result	Direct fix: 0.10 (H)
Additional Acoustic Information	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	6
Colour Fastness to Rubbing Standard Test Method	ISO 105 - X12
Colour Fastness to Rubbing Rating	Wet: 5, Dry: 5

Sustainability

VOC Emissions Results	ASTM D5116: TVOC Emissions Rate: <0.02mg/m^2/hr (7 days)
Sustainability Performance	

Copyright Woven Image

Instructions

Additional Information	See Woven Image Mura Care & Cleaning Guide, and Installation Guide. Please note: The face of Mura is smooth and the back is fluffy. Mura is rolled Face out on the core. Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.

Copyright Woven Image