

EchoFlex™

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition 100% PET (24% post-consumer recycled)

Colours Available 22

Dimensions & Weight

Dimensions Panel Length: 2400mm (+/-30mm); 2800mm (+/-30mm), Width: 1220mm (+/-2mm), Thickness 10-12mm (+/-2mm) Roll Length: 25m (+/-25mm) Width: 1220mm (+/-2mm) Thickness 10-12mm (+/-2mm)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 4.68

Performance

Fire Test Result ISO 9705: Group 1, For further information contact designlink@csr.com.au

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17

Noise Reduction Coefficient (NRC) Result Direct fix: 0.40 when adhered to 10mm plasterboard

Sound Absorption Average (SAA) Result	Direct fix: 0.41 when adhered to 10mm plasterboard
Weighted Sound Absorption Coefficient (αw) Result	Direct fix: 0.35 (H) when adhered to 10mm plasterboard
Sound Absorption Class	D (Direct fix) when adhered to 10mm plasterboard

Sustainability

VOC Emissions Results CDPH Standard Method v1.2 – 2017 (CA 01350): TVOC Range 0.5mg/m³ or less; Refer to Intertek Clean Air certificate

Sustainability Performance



Instructions

Additional Information See Woven Image EchoFlex Care & Cleaning Guide, and Installation Guide.

EchoFlex has a non-woven hook and loop fabric with nap and no pattern repeat. Take care the nap runs in the same direction during installation.

Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.