Nalu Embossed Panel

Designer: Woven Image

Application(s): Walls, Ceilings

Composition & Pattern

Composition	98.5% PET (50% post-consumer recycled) & 1.5% PE
Colours Available	19
Pattern Type	Embossed

Dimensions & Weight

Dimensions	Length: 2800mm (+/-3 mm), Width: 1130mm (+/- 3mm), Thickness: 9mm (+/- 7%)
Unit of Sale	Panel
Unit of Sale Net Weight (kg)	7.5

Performance

Fire Test Result	AS ISO 9705 & AS 5637.1: Group 1. SMOGRArc <100 (m^2/s^2x1000), C/VM2 - Verification Method - Group 1-S. Average smoke production rate (m^2/s) <5, For further information contact designlink@csr.com.au
Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016)

Copyright Woven Image

Noise Reduction Coefficient (NRC) Result	Direct fix: 0.40
Sound Absorption Average (SAA) Result	Direct fix: 0.39
Weighted Sound Absorption Coefficient (αw) Result	Direct fix: 0.25 (MH)
Sound Absorption Class	E (Direct fix)


Sustainability

VOC Emissions Results	CDPH Standard Method v1.2 – 2017 (CA 01350): TVOC Range 0.5mg/m^3 or less; Refer to Intertek Clean Air certificate
Sustainability Performance	

Instructions

Additional Information	For direct fix wall and ceiling applications only. See Woven Image Embossed Panels Installation Guide. See Woven Image Embossed Panels Care & Cleaning Guide. Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.

Copyright Woven Image



Copyright Woven Image