Zen Embossed Panel

Designer: Woven Image

Application(s): Walls, Ceilings

Composition & Pattern

Composition	98.5% PET (50% post-consumer recycled) & 1.5% PE
Colours Available	25
Pattern Type	Embossed

Dimensions & Weight

Dimensions	Length: 2800mm (+/-3mm), Width: 1130mm (+/- 3mm), Thickness: 9mm (+/- 7%)
Unit of Sale	Panel
Unit of Sale Net Weight (kg)	7.5

Performance

Fire Test Result	AS ISO 9705 & AS 5637.1: Group 1. SMOGRArc <100 (m^2/s^2x1000), C/VM2 - Verification Method - Group 1-S. Average smoke production rate (m^2/s) <5, For further information contact designlink@csr.com.au
Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016)

Copyright Woven Image

Noise Reduction Coefficient (NRC) Result	Direct fix: 0.30
Sound Absorption Average (SAA) Result	Direct fix: 0.28
Weighted Sound Absorption Coefficient (αw) Result	Direct fix: 0.20 (H)
Sound Absorption Class	E (Direct fix)
Additional Acoustic Information	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency

Sustainability

VOC Emissions Results	CDPH Standard Method v1.2 – 2017 (CA 01350): TVOC Range 0.5mg/m^3 or less; Refer to Intertek Clean Air certificate
Sustainability Performance	


Instructions

Additional Information	For direct fix wall and ceiling applications only. See Woven Image Embossed Panels Installation Guide. See Woven Image Embossed Panels Care & Cleaning Guide.

Copyright Woven Image

Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.

To assist in accurate pattern matching on a continuous wall, ZEN has been trimmed on all four sides with a unique 5 degree bevel as shown below. Dimensions shown in millimetres.



Copyright Woven Image