

Kaleidoscope Tile

Designer: Woven Image (Amy Saunders)

Application(s): Walls

Composition & Pattern

Composition 100% PET (68% recycled)

Colours Available 6

Pattern Type Printed

Printed Sides Single

Print Area Horizontal: 550mm, Vertical: 550mm

Print Tolerance Horizontal: +/-2mm, Vertical: +/-2mm

Pattern Repeat One tile

Kit & Box Content

Quantity in Box 10

Dimensions & Weight

Dimensions Length: 550mm (+/- 2mm), Width: 550mm (+/- 2mm), Thickness: 9mm (+/- 7%)

Unit of Sale Box

Performance

Fire Test Result	ISO 9705: Group 1, GB 8624 B1, BS EN 13501.1: Classification C - s1, d2, ASTM E84 Unadhered: Class 2 or B
Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016)
Noise Reduction Coefficient (NRC) Result	Direct fix: 0.30
Sound Absorption Average (SAA) Result	Direct fix: 0.32
Weighted Sound Absorption Coefficient (α_w) Result	Direct fix: 0.25 (H)
Sound Absorption Class	D (Direct fix)
Additional Acoustic Information	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	6
Colour Fastness to Rubbing Standard Test Method	ISO 105 - X12
Colour Fastness to Rubbing Rating	Wet: 4 - 5, Dry: 5

Sustainability

VOC Emissions Results	ASTM D5116: TVOC Emissions Rate: <0.023mg/m ² /hr (7 days)
------------------------------	---

Sustainability Performance



Instructions

Product Care Instructions See Woven Image Tiles Installation Guide