

Mura Haku & Kome

Designer: Akira Isogawa in collaboration with Woven Image

Application(s): Workstations, Walls, Partitions

Composition & Pattern

Composition	100% PET (60% post-consumer recycled)
Colours Available	4
Weave	Non woven
Pattern Type	Printed
Printed Sides	Single
Pattern Repeat	Horizontal: 14.5cm, Vertical: 20cm

Dimensions & Weight

Dimensions	Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m
Unit of Sale	Linear metre
Unit of Sale Net Weight (kg)	0.424

Performance

Fire Test Result	ASTM E84 Adhered: Class 1 or A, BS 476: Class 2, BS EN 13501.1:
-------------------------	---

Classification B - s1, d0, BS EN 45545-2 + A1 Annex C: CIT: 0.00,
ISO 9705: Group 1

Acoustic Performance Standard Test Method	AS ISO 354: 2006 (R2016)
Noise Reduction Coefficient (NRC) Result	Direct fix: 0.10
Sound Absorption Average (SAA) Result	Direct fix: 0.08
Weighted Sound Absorption Coefficient (α_w) Result	Direct fix: 0.10 (H)
Additional Acoustic Information	Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	6
Colour Fastness to Rubbing Standard Test Method	ISO 105 - X12
Colour Fastness to Rubbing Rating	Wet: 5, Dry: 5

Sustainability

VOC Emissions Results Mura Haku achieves ASTM D5116: TVOC Emissions Rate: <0.031mg/m²/hr (7 days), and Mura Kome achieves ASTM D5116: TVOC Emissions Rate: <0.02mg/m²/hr (7 days)

Sustainability Performance



Environmental Product Declaration (EPD)

Instructions

Product Care Instructions See Woven Image Mura Installation Guide