

Mura

Designer: Woven Image

Application(s): Walls, Workstations, Partitions

Composition & Pattern

Composition 100% PET (60% post-consumer recycled)

Colours Available 23

Dimensions & Weight

Dimensions Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m and 105m

Unit of Sale Linear metre

Unit of Sale Net Weight (kg) 0.424

Performance

Fire Test Result ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS 476: Class 2, ASTM E84 Adhered: Class 1 or A, BS EN 45545-2 + A1 Annex C: CIT: 0.00

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016)

Noise Reduction Coefficient (NRC) Result Direct fix: 0.10

Sound Absorption Average (SAA) Result Direct fix: 0.08

Weighted Sound Absorption Coefficient (αw) Result Direct fix: 0.10 (H)

Additional Acoustic Information Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency

Colour Fastness to Light Standard Test Method ISO 105 B02

Colour Fastness Light Rating 6

Colour Fastness to Rubbing Standard Test Method ISO 105 - X12

Colour Fastness to Rubbing Rating Wet: 5, Dry: 5

Sustainability

VOC Emissions Results ASTM D5116: TVOC Emissions Rate: <0.02mg/m²/hr (7 days)

Sustainability Performance



Instructions

Product Care Instructions See Woven Image Mura Care & Cleaning Guide, and Installation Guide