

GEM Panel

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition 100% PET (60% recycled)

Colours Available 15

Pattern Type Embossed

Dimensions & Weight

Product Width (mm) 1130

Product Width Tolerance (mm) +/- 2mm

Product Length (mm) 2800

Product Length Tolerance (mm) +/- 2mm

Additional Dimension Details Length: 2800mm (+/-2 mm), Width: 1130mm (+/- 2mm), Thickness: 9mm (+/- 7%)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 7.83

Performance

Fire Test Result ASTM E84 Unadhered: Class 1 or A, BS EN 13501.1: Classification B - s2,d0

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016)

Noise Reduction Coefficient (NRC) Result Direct fix: 0.30, 20mm air gap: 0.50, 50mm air gap: 0.65
Achieves an NRC of 0.70 - 0.75 and α_w of 0.75 with a 15mm and 25mm acoustic infill respectively

Sound Absorption Average (SAA) Result Direct fix: 0.28

Weighted Sound Absorption Coefficient (α_w) Result Direct fix: 0.20 (H), 20mm air gap: 0.45 (MH), 50mm air gap: 0.70 (MH)

Sound Absorption Class E (Direct fix)

Additional Acoustic Information Key: H = High Frequency / MH = Mid to High Frequency

Colour Fastness to Light Standard Test Method ISO 105 B02

Colour Fastness Light Rating 6

Colour Fastness to Rubbing Standard Test Method ISO 105 - X12

Colour Fastness to Rubbing Rating Wet: 4 - 5, Dry: 5

Sustainability

VOC Emissions Results ASTM D5116: TVOC Emissions Rate: 0.023mg/m²/hr (7 days)

Sustainability Performance



Declare.



Instructions

Product Care Instructions See Woven Image Embossed Panels Care & Cleaning Guide, and Installation Guide

