

# Terrain

**Designer:** Woven Image

**Application(s):** Walls

## Composition & Pattern

**Composition** 50% Flax & 50% Polypropylene

**Colours Available** 2

**Weave** Non woven

## Dimensions & Weight

**Dimensions** Length: 2800mm (+/- 2mm), Width: 1100mm (+/- 2mm), Thickness: 2.5mm (+/- 7%)

**Unit of Sale** Panel

**Unit of Sale Net Weight (kg)** 2

## Performance

**Fire Test Result** AS 3837: Group 3, ASTM E84 Unadhered: Class 2 or B

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016)

**Noise Reduction Coefficient (NRC) Result** Direct fix: 0.05

**Sound Absorption Average (SAA)** Direct fix: 0.06  
**Result**

**Weighted Sound Absorption Coefficient ( $\alpha_w$ )** Direct fix: 0.05 (H)  
**Result**

**Additional Acoustic Information** Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency

**Colour Fastness to Light Standard** ISO 105 B02  
**Test Method**

**Colour Fastness Light Rating** 4 - 5

## Sustainability

**VOC Emissions Results** ASTM D5116: TVOC Emissions Rate: <0.02mg/m<sup>2</sup>/hr(7 days)

**Sustainability Performance**



## Instructions

**Additional Information** See Woven Image Terrain & Orbit Care & Cleaning Guide, and Installation Guide.

Exact colour matching cannot be guaranteed between batches.