Report Number: 39189 Date:3-1-10

For the Account Of:	Woven Image 37-39 Chard Road Brookvale 2100
Contact:	Sydney, Australia Sarah Spence

Client's Identification: Outdoor Fine

Test Performed California Technical Bulletin 117, Section E (CPSC 16 CFR 1610 – CS 191-53) Upholstery Fabrics

TEST DATA

Raised Surface

—	—	
	Flame Spread	Flame Spread
	Warp Face	Warp Back
Specimen	(seconds)	(seconds)
1	DNI	
2	DNI	
3	DNI	
4		DNI
5		DNI
	Flame Spread	Flame Spread
	Fill Face	Fill Back
Specimen	(seconds)	(seconds)
1	DNI	
2	DNI	
3	DNI	
4		DNI

4	4	DNI
Ę	5	DNI

ABBREVIATIONS USED

DNI Did not ignite when exposed to test ignition source

- **IBE** Ignited but extinguished before burning through stop cord
- SF Surface flash only; stop cord not burned & no burning/charring/fusing of the base fabric
- TSF Timed surface flash; stop cord burned, but no burning/charring/fusing of the base fabric

ACCEPTANCE CRITERIA

- 1. With nap Minimum flame spread of any individual specimens shall be 7 seconds.
- 2. Without nap Minimum flame spread of any individual specimens shall be 3.5 seconds.

CONCLUSION Based on the above Results and Acceptance Criteria, the item tested:

- 🛛 Complies
- Does Not Comply

CERTIFICATION: I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Authorized Signature