



Report Number: 57935

Date: 04-12-2013

For the Account Of:

Woven Image Pty Ltd.

37-39 Chard rd, Brookvale NSW 2100

Australia

Contact:

Amy Saunders

Client's Identification:

Mono CR with Crypton

Test Performed

California Technical Bulletin 117, Section E (CPSC 16 CFR 1610 - CS 191-53) Upholstery

Fabrics, March 2000

TEST DATA

☐ Raised Surface

	Flame Spread	Flame Spread
	Warp Face	Warp Back
Specimen	(seconds)	(seconds)
1	DNI	
2	DNI	
3	DNI	
4		DNI
5		DNI

	Flame Spread	Flame Spread
	Fill Face	Fill Back
Specimen	(seconds)	(seconds)
1	DNI	
2	DNI	
3	DNI	
4		DNI
5		DNI

ABBREVIATIONS USED

DNI Did not ignite when exposed to test ignition source

IBE Ignited but extinguished before burning through stop cord

SF Surface flash only; stop cord not burned & no burning/charring/fusing of the base fabric

Timed surface flash; stop cord burned, but no burning/charring/fusing of the base fabric

ACCEPTANCE CRITERIA

- With nap Minimum flame spread of any individual specimens shall be 7 seconds. (ACT Criteria decreases minimum time to 4 seconds)
- 2. Without nap Minimum flame spread of any individual specimens shall be 3.5 seconds.

CONCLUSION

TSF

Based on the above Results and Acceptance Criteria, the item tested:

□ Complies

☐ Does Not Comply

CERTIFICATION: I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

C. Varthiner

Authorized Signature-MB