

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 1

Received:06/0	4/2015 Completed: 06/05/2015	Letter: C7	MB	P.O.#: 15-0055941	Test Report #		3-08257-7-
Client's Identification	Fabric Name: Ravenna. Part #: Jacquard. Backing: Acrylic. Fin					d. Constructi	on:
Tested For: Sarah Bucke			Key Test: NFPA 260 Cover Fabric (BLDG)				235
F	Knoll Inc.						
1	235 Water Street			Tel:	1-(215)-679-1224	Ext:	
E	E Greenville, PA 18041			Fax:	1-(215)-679-1600		

CLIENT'S IDENTIFICATION (continuation):

End Use: Upholstery.

Category: NFPA 260 Fabric LE 2013; V 03/15 NE:2018 PC: 4H

dl/jd

NFPA 101

LE 2015; V 04/15

LE 2015; V 03/15

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture;

Cover Fabric Test

SPECIMEN TEST COMPOSITE:

Candidate cover fabric (see "Client's Identification")

Standard filling material: Non FR polyurethane foam, density 20 kg/m³ to 25 kg/m³

RESULTS:

	TEST	(1	RETEST (If Re	•
l .				
		Char Length	9	Char Length
	Ignition	On Vertical	Ignition	On Vertical
Specimen #	(yes/no/SE)	Panel (mm)	(yes/no/SE)	Panel (mm)
1	No	16		N 98
2	No 4	20		
3	No	18		

ABBREVIATION WHICH MAY BE USED:

- SE = Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.
- EC = Escalating combustion. Specimen extinguished by technician. No char length measurement taken.

CLASSIFICATION SYSTEM:

- Class I For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)
- Class II For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 2

Received:06/04/2015 Complete	ed:06/05/2015	Letter: C7	MB	P.O.#: 15-0055941	Test Report	#:	3-08257-7-	
Client's Fabric Name: Ravenna. Part #: K2051. Content: 55% Polyester, 45% Acrylic. Weight: 22.5 oz/linyd. Construction: Identification Jacquard. Backing: Acrylic. Finish: Soil + Stain Repellent. (see continuation)								
Tested For: Sarah Bucke Knoll Inc.				Key Test:	NFPA 260 Cover Fa	abric (BLDG)	235	
1235 Water Street E Greenville, PA					1-(215)-679-1224 1-(215)-679-1600	Ext:		

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

(x) Class I rating; [] Class II rating

REMARKS: None.

CODE INFORMATION: In accordance with --

(1) The 2015 Edition of the NFPA Life Safety Code 101, paragraph 10.3.2.1(1); and

(2) The 2015 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1, 805.3.1.1, and 805.4.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

Detention or correctional occupancy Health care occupancy Residential board & care occupancy College and university dormitories

COMMENTARY: The cigarette ignition source used in this test conforms to the physical parameters set forth in the test standard. The actual propensity of the cigarette (that is currently manufactured) to cause ignition of materials under test might be different than the cigarette that was manufactured at the inception of the test standard.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 260.

MS. PHYLLIS PETTIT

THORIZED SIGNATURE

JUN 1 8 2015

SOVMARK /ec/1/9

(Page 2 of 2)