

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 1

Received: 10	06/2016	Completed: 10/11/2016	Letter: N7	BG	P.O.#: 16-0056053	Test Report #:	3	-15738-7-
Client's Identification		K2150 "Multi Wool Plaid Upholstery.	d". Compositio	on: 55%	Rayon, 42% Wool, 3% N	lylon, Weight: 22.85 (oz./linyd. Pr	oduct End
Tested For:	Sarah Bucke Knoll Inc.		V-04	Key Test: NFPA 260 Cover Fabric (BLDG)			235	
	1235 W	ater Street ville, PA 18041				(215)-679-1224 (215)-679-1600	Ext:	

Category: NFPA 260 Fabric

LE 2013; V 03/15 NE:2018 PC: 4H NTR 04/16 dl/jd

NFPA 101

LE 2015; V 04/15

LE 2015; V 03/15

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition

Resistance of Components of Upholstered Furniture;

Cover Fabric Test

SPECIMEN TEST COMPOSITE:

Candidate cover fabric (see "Client's Identification")

Standard filling material: Non FR polyurethane foam, density 20 kg/m³ to 25 kg/m³

	TEST		RETEST (If Re	equired)		
-						
Specimen #	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)		

1	No	10				
2	No	12				
3	No	12				

ABBREVIATION WHICH MAY BE USED:

- SE = Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.
- EC = Escalating combustion. Specimen extinguished by technician. No char length measurement taken.

CLASSIFICATION SYSTEM:

- Class I For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)
- Class II For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

[x] Class I rating; [] Class II rating

(Page 1 of 2)



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 2

Received: 10/06/2016 Completed: 10/11/2016 Letter: N7	BG P.O.#: 16-0056053 Test Report #: 3-1	5738-7-	
Client's Style: K2150 "Multi Wool Plaid". Compositi Identification Use: Upholstery.	on: 55% Rayon, 42% Wool, 3% Nylon. Weight: 22:85 oz./linyd. Prod	uct End	
Tested For: Sarah Bucke Knoll Inc.	Key Test: NFPA 260 Cover Fabric (BLDG)		
1235 Water Street E Greenville, PA 18041	Tel: 1-(215)-679-1224 Ext: Fax: 1-(215)-679-1600		

REMARKS: None

CODE INFORMATION: In accordance with --

(1) The 2015 Edition of the NFPA Life Safety Code 101, paragraph 10.3.2.1(1); and

(2) The 2015 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1, 805.3.1.1, and 805.4.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

Detention or correctional occupancy Health care occupancy Residential board & care occupancy College: and university dormitories

COMMENTARY: The digarette ignition source (SRM 1196) used in this test conforms to the physical parameters set forth in the test standard. The actual propensity of the digarette (that is currently manufactured) to cause ignition of materials under test might be different than the digarette that was manufactured at the inception of the test standard.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

GOVMARK

/pm /mo

Ms. Phyllo Petrit

OCT 1 7 2016

(Page 2 of 2)