

Terrain

Designer: Woven Image

Application(s): Walls

Composition & Pattern

Composition 50% Flax & 50% Polypropylene

Colours Available 2

Weave Non woven

Dimensions & Weight

Dimensions Length: 2800mm (+/- 2mm), Width: 1100mm (+/- 2mm), Thickness: 2.5mm (+/- 7%)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 2

Performance

Fire Test Result AS 3837: Group 3, ASTM E84 Unadhered: Class 2 or B

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016)

Noise Reduction Coefficient (NRC) Result Direct fix: 0.05

Sound Absorption Average (SAA) Direct fix: 0.06
Result

Weighted Sound Absorption Direct fix: 0.05 (H)
Coefficient (α_w) Result

Additional Acoustic Information Noise reduction coefficient result key: H = High Frequency / MH =
Mid to High Frequency

Colour Fastness to Light Standard ISO 105 B02
Test Method

Colour Fastness Light Rating 4 - 5

Sustainability

VOC Emissions Results ASTM D5116: TVOC Emissions Rate: <0.02mg/m²/hr (7 days)

Sustainability Performance



Instructions

Additional Information See Woven Image Terrain & Orbit Care & Cleaning Guide, and
Installation Guide.

Exact colour matching cannot be guaranteed between batches.