

Mura

Designer: Woven Image

Application(s): Walls, Workstations, Partitions

Composition & Pattern

Composition 100% PET (60% post-consumer recycled)

Colours Available 23

Dimensions & Weight

Dimensions Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m and 105m

Unit of Sale Linear metre

Unit of Sale Net Weight (kg) 0.424

Performance

Fire Test Result ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS 476: Class 2, ASTM E84 Adhered: Class 1 or A, BS EN 45545-2 + A1 Annex C: CIT: 0.00

Acoustic Performance Standard Test Method AS ISO 354: 2006 (R2016)

Noise Reduction Coefficient (NRC) Result Direct fix: 0.10

Sound Absorption Average (SAA) Direct fix: 0.08
Result

Weighted Sound Absorption Direct fix: 0.10 (H)
Coefficient (αw) Result

Additional Acoustic Information Noise reduction coefficient result key: H = High Frequency / MH =
Mid to High Frequency

Colour Fastness to Light Standard ISO 105 B02
Test Method

Colour Fastness Light Rating 6

Colour Fastness to Rubbing Standard ISO 105 - X12
Test Method

Colour Fastness to Rubbing Rating Wet: 5, Dry: 5

Sustainability

VOC Emissions Results ASTM D5116: TVOC Emissions Rate: <0.02mg/m²/hr (7 days)

Sustainability Performance



Instructions

Additional Information See Woven Image Mura Care & Cleaning Guide, and Installation Guide.

Please note: The face of Mura is smooth and the back is fluffy.
Mura is rolled Face out on the core.

Exact colour matching cannot be guaranteed between batches.
Fibre mix and web variation are natural characteristics of this product.