

# Mura Otto

**Designer:** Woven Image

**Application(s):** Workstations, Walls, Partitions

## Composition & Pattern

**Composition** 100% PET (60% post-consumer recycled)

**Colours Available** 7

**Weave** Non woven

**Pattern Type** Printed

**Printed Sides** Single

**Pattern Repeat** Horizontal: 1.5cm, Vertical: 2cm

## Dimensions & Weight

**Dimensions** Length: 25m, Width: 1210mm (+/- 5mm), Thickness: 1.9mm (+/- 0.25mm) Also available in lengths of 6m

**Unit of Sale** Linear metre

**Unit of Sale Net Weight (kg)** 0.424

## Performance

**Fire Test Result** ASTM E84 Adhered: Class 1 or A, BS 476: Class 2, BS EN 13501.1:

Classification B - s1, d0, ISO 9705: Group 1, BS EN 45545-2 + A1  
Annex C: CIT: 0.00

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016)

**Noise Reduction Coefficient (NRC) Result** Direct fix: 0.10

**Sound Absorption Average (SAA) Result** Direct fix: 0.08

**Weighted Sound Absorption Coefficient ( $\alpha_w$ ) Result** Direct fix: 0.10 (H)

**Additional Acoustic Information** Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency

**Colour Fastness to Light Standard Test Method** ISO 105 B02

**Colour Fastness Light Rating** 6

**Colour Fastness to Rubbing Standard Test Method** ISO 105 - X12

**Colour Fastness to Rubbing Rating** Wet: 5, Dry: 5

## Sustainability

**VOC Emissions Results** ASTM D5116: TVOC Emissions Rate: <0.02mg/m<sup>2</sup>/hr (7 days)

### Sustainability Performance



## Instructions

**Additional Information** See Woven Image Mura Installation Guide.

Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.