

# Balance 1340 Tile

**Designer:** Woven Image

**Application(s):** Walls, Ceilings

## Composition & Pattern

**Composition** 100% PET (60% post-consumer recycled)

**Colours Available** 14

## Kit & Box Content

**Quantity in Box** 6

## Dimensions & Weight

**Dimensions** Length: 1340mm (+/-2 mm), Width: 335mm (+/- 2mm), Thickness: 24mm (+/- 7%)

**Unit of Sale** Box

**Unit of Sale Net Weight (kg)** 9

## Performance

**Fire Test Result** ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS EN 45545-2 + A1 Annex C: CIT: 0.00, ASTM E84 Unadhered: Class 1 or A

**Acoustic Performance Standard Test Method** AS ISO 354: 2006 (R2016)

**Noise Reduction Coefficient (NRC) Result** Direct fix: 0.65

**Sound Absorption Average (SAA) Result** Direct fix: 0.63

**Weighted Sound Absorption Coefficient ( $\alpha_w$ ) Result** Direct fix: 0.45 (MH)

**Sound Absorption Class** D (Direct fix)

**Additional Acoustic Information** Sound Absorption Class result is based on EchoPanel® 24mm. MH = Mid to High Frequency.

**Colour Fastness to Light Standard Test Method** ISO 105 B02

**Colour Fastness Light Rating** 6 - 7

## Sustainability

**VOC Emissions Results** EchoPanel 24mm achieves ASTM D5116: TVOC Emissions Rate:  $<0.02\text{mg}/\text{m}^2/\text{hr}$  (7 days), and CDPH Standard Method v1.2: TVOC Emissions Rate:  $<0.054\text{mg}/\text{m}^3$ ; Formaldehyde Emissions Rate:  $<2\mu\text{g}/\text{m}^3$

**Sustainability Performance**



**Sustainability Performance Details** EchoPanel achieves GreenTag Certification GreenRate: Level A &

Health Rate Platinum, Red List Free, and has an International Living Future Institute Declare Label.

## Instructions

**Additional Information** See Woven Image EchoPanel Care & Cleaning Guide.  
See Woven Image Tiles Installation Guide.

Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.

