

EchoPanel® Parquet

Designer: Woven Image

Application(s): Walls, Partitions

| Composition & Pattern | |
|------------------------|--|
| Composition | 100% PET (60%-80% post-consumer recycled)* |
| Colours Available | 34 |
| Pattern Type | Precision Cut |
| Additional Information | *As part of our ongoing commitment to sustainability, we are increasing the amount of post-consumer PET in EchoPanel 12mm, from 60% to 80%. We anticipate all stock to have transitioned by January 2025. |

| Dimensions & Weight | |
|------------------------------|--|
| Dimensions | Length: 2750mm (+/-2 mm), Width: 1100mm (+/- 2mm), Thickness: 12mm (+/- 7%). Also available in 24mm (+/-7%), specifications will differ. |
| Unit of Sale | Panel |
| Unit of Sale Net Weight (kg) | 7.1 |

Performance

Fire Test Result AS 1530.3, BS EN 13501.1: Classification B - s1, d0, ISO 9705: Group

| | 1, BS EN 45545-2 + A1 Annex C: CIT: 0.03, ASTM E84 Unadhered: Class 1 or A, GB 8624 B1 | | |
|--|--|--|--|
| Acoustic Performance Standard Test Method | AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17 | | |
| Noise Reduction Coefficient (NRC) Result | | | |
| Sound Absorption Average (SAA) Result | | | |
| Weighted Sound Absorption Coefficient (aw) Result | | | |
| Sound Absorption Class | D(Direct fix), D(20mm air gap), C(50mm air gap) | | |
| Additional Acoustic Information | Noise reduction coefficient result key: H = High Frequency / MH = Mid to High Frequency | | |
| Colour Fastness to Light Standard Test Method | ISO 105 B02 | | |
| Colour Fastness Light Rating | 6 - 7 | | |

Sustainability

| | VOC Emissions Results | Formaldehyde Emissi | ons Rate: 0.008mg/m A 01350): TVOC Emissi | 1.080mg/m²/hr (24hrs); h²/hr. CDPH Standard ons Rate: 0.010mg/m³; |
|---|----------------------------|---|--|---|
| Ş | Sustainability Performance | Climate Active Carbon Neutral PRODUCT | CERTIFICO CERTIFICO CERTIFICO CERTIFICO COMMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION COMUNICATION C | REALTH RATE Plathurn Plathurn Fishur trust brands |
| | | Declare. | Red List Free | Low VOC |
| | | | | |

| Additional Information | See Woven Image EchoPanel® Care & Cleaning Guide. See Woven Image EchoPanel® Precision Cut Panels Installation Guide. |
|------------------------|--|
| | Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product. |

