



# EchoPanel® Trio

Designer: Woven Image

Application(s): Walls, Workstations, Partitions

## Composition & Pattern

**Composition** 100% PET (60%-80% post-consumer recycled)\*

Colours Available 20

Weave Non woven

Pattern Type Printed

Printed Sides Single

Print Area Horizontal: 2780mm, Vertical: 1180mm

**Print Tolerance** Horizontal: +/-2mm, Vertical: +/-2mm

Pattern Repeat Horizontal: 63mm, Vertical: 63mm

**Additional Information** \*As part of our ongoing commitment to sustainability, we are

increasing the amount of post-consumer PET in EchoPanel 12mm, from 60% to 80%. We anticipate all stock to have transitioned by

March 2025.

### Dimensions & Weight

**Dimensions** Length: 2800mm (+/- 10mm), Width: 1200mm (+/- 5mm),

Thickness: 12mm (+/- 7%)

Unit of Sale Panel

Unit of Sale Net Weight (kg) 8

P	٥r	·fo	rr	ทล	nc	0
$\Box$	-1		111	114	111	. $\vdash$

Fire Test Result AS 1530.3, BS EN 13501.1: Classification B - s1, d0, ISO 9705: Group

1, GB 8624 B1, ASTM E84 Unadhered: Class 1 or A, BS EN 45545-2 +

A1 Annex C: CIT: 0.05

Method

Acoustic Performance Standard Test AS ISO 11654: 2002 (2016), AS ISO 354: 2006 (R2016), ASTM C423 - 17

Noise Reduction Coefficient (NRC)

Direct fix: 0.45, 20mm air gap: 0.60, 50mm air gap: 0.75

Result

Sound Absorption Average (SAA)

Direct fix: 0.43, 20mm air gap: 0.61, 50mm air gap: 0.75

Weighted Sound Absorption

Direct fix: 0.30 (MH), 20mm air gap: 0.45 (MH), 50mm air gap: 0.60

Coefficient (aw) Result

Sound Absorption Class D (Direct fix), D (20mm air gap), C (50mm air gap)

Additional Acoustic Information Noise reduction coefficient result key: H = High Frequency & MH =

Mid to High Frequency

Colour Fastness to Light Standard

**Test Method** 

ISO 105 B02

Colour Fastness Light Rating 6 - 7

**Other Testing** Fire tests are based on plain EchoPanel® 12mm

#### Sustainability

**Additional Information** As Per EchoPanel 12mm plain: ASTM D5116 - 2017: TVOC Emissions

Rate: 0.033mg/m<sup>2</sup>/hr(24hrs); Formaldehyde Emissions Rate: 0.07mg/m<sup>2</sup>/hr. CDPH Standard Method v1.2 - 2017 (CA 01350): TVOC Emissions Rate: 0.013mg/m<sup>3</sup>; Formaldehyde Emissions Rate:

 $<1\mu g/m^3$ 


## Instructions

#### Additional Information

See Woven Image EchoPanel® Installation Guide.

See Woven Image EchoPanel® prints Care & Cleaning guide.

Exact colour matching cannot be guaranteed between batches. Fibre mix and web variation are natural characteristics of this product.



Please note there is an unprinted boarder of approx 10mm around the panel.
Panels will require trimming for edge to edge pattern matching.

